AKAI SERVICE MANUAL

STEREO TAPE DECK

4000DS

4000DS Mk-II

STEREO TAPE DECK

MODEL 4000DS

SECTION 1

SERVICE MANUAL

TABLE OF CONTENTS

I. SPECIFICATIONS

An asterisk next to a figure indicates the minimum guaranteed performance.

TRACK SYSTEM		4-track 2-channel stereo/monaural system
REEL CAPACITY		Up to 7" reel
TAPE SPEED		7-1/2 and 3-3/4 ips ± 2% (*±3%)
WOW AND FLUTTER		Less than 0.15% (*0.22%) RMS at 7-1/2 ips Less than 0.20% (*0.30%) RMS at 3-3/4 ips
FREQUENCY RESPONSE	AKAI SRT tape	30 to 23,000 Hz (*40 to 22,000 Hz) ± 3 dB at 7-1/2 ips 30 to 16,000 Hz (*40 to 14,000 Hz) ± 3 dB at 3-3/4 ips
	Regular tape	30 to 20,000 Hz (*40 to 20,000 Hz) ± 3 dB at 7-1/2 ips 30 to 14,000 Hz (*40 to 14,000 Hz) ± 3 dB at 3-3/4 ips
SIGNAL TO NOISE RATIO		Better than 50 dB at 7-1/2 ips Better than 48 dB at 3-3/4 ips
DISTORTION		Less than 1.5% (*2.0%) at 7-1/2 ips Less than 2.5% at 3-3/4 ips
CROSS TALK		Better than 70 dB (*60 dB) monaural Better than 50 dB (*45 dB) stereo
ERASE RATIO		Better than 70 dB
INPUTS	Mic input	0.8 mV Impedance 5 kΩ
	Line input	70 mV Impedance 150 kΩ
	Din input	7 mV
OUTPUTS	Line output	1.228V (4 ± 1 dB) using a 250 Hz "0" VU recorded tape
	Din output	0.4V
BIAS FREQUENCY		105 kHz ± 5%
BIAS LEAK		Less than -30 VU
HIGH FREQUENCY DEVIATION		Within 2 dB using an 8,000 Hz 3-3/4 ips recorded tape at 7-1/2 ips
RECORDING CAPACITY		60 min. stereo recording using a 1,200 ft. tape at 7-1/2 ips
FAST FORWARD AND REWIND TIME		152/190 sec. using a 1,200 ft. tape at 60/50 Hz
MOTOR		4-pole induction 1-speed motor Type: SSM-1 Revolutions: 1,800/1,500 rpm. at 60/50 Hz
HEADS	Recording Head	In-line 4-track 2-channel recording head Type: P4-154 Gap: 1 micron Impedance: 95Ω ± 15% at 1,000 Hz
	Playback Head	In-line 4-track 2-channel playback head Type: P4-150 Gap: 1 micron Impedance: 1,250Ω ± 15% at 1,000 Hz
	Erase Head	In-line 4-track 2-channel erase head Type: E4-200 Gap: 0.6 mm Impedance: 200Ω ± 5% at 100 kHz
TRANSISTORS		6 ..... 2SC458 LG (C) (D) — 2 ..... 2SC971 (2) (3) (red) 2 ..... 2SC871 (E) (F) — 1 ..... 2SC1098 (L) (M)
IC		4 ..... LD3141
DIODES		2 ..... 1N34A 1 ..... 10DC-1 1 ..... 1S339A
POWER SUPPLY		100 to 240V A.C., 50/60 Hz 120V A.C., 60 Hz for CSA/UL Models 220V A.C., 50 Hz for CEE model
POWER CONSUMPTION		35W
INSULATION RESISTANCE		More than 50 MΩ
INSULATION DURABILITY		1,000V A.C. for more than 1 min. duration
DIMENSIONS		406 (W) X 314 (H) X 194 (D) mm (15.9" X 12.4" X 7.6")
WEIGHT		11.4 kg (25 lbs.)

NOTE: Specifications subject to change without notice.

II. MEASURING METHOD

1. TAPE SPEED DEVIATION



Fig. 1

As shown in Figure 1, connect a Frequency Counter to the Line Output of Model 4000DS.
Take a frequency counter reading at the beginning, middle, and end of tape winding during playback. The maximum value of these respective readings will represent tape speed deviation.

2. WOW AND FLUTTER



Fig. 2

Method A
As shown in Fig. 2, connect the Line Output of Model 4000DS to the Input of a Wow and Flutter Meter. Use a 3,000 Hz pre-recorded test tape and take a wow and flutter meter reading at the beginning, middle, and end of tape winding. The maximum value of these respective readings will represent the wow and flutter.

Method B
Supply a 3,000 Hz sine wave signal from an Audio Frequency Oscillator and make a recording on a blank tape at the beginning, middle, and end of tape winding. Rewind and playback tape. Measure wow and flutter with a Wow and Flutter Meter. (The wow and flutter value of Method B will be close to twice that of Method A.)

3. FREQUENCY RESPONSE



Fig. 3

For measuring frequency response, connect instruments as shown in Fig. 3 and proceed as follows:

1) Supply a 1,000 Hz sine wave to the Line Input of Model 4000DS from an Audio Frequency Oscillator through an Attenuator. Set recorder to recording mode and turn recording level volume control to maximum. Adjust Attenuator to obtain a +4 dB V.T.V.M. reading.
2) Under conditions described in 1) above, re-adjust Attenuator so that the Line Output is -16 dB, and record 40 to 20,000 Hz spot frequencies.
3) Rewind tape and playback from the beginning. Take V.T.V.M. spot frequency readings and plot values on a graph.

NOTE: When measuring frequency response, new tape should be used.

4. SIGNAL TO NOISE RATIO



Fig. 4

As shown in Fig. 4, connect a High Sensitivity V.T.V.M. to the Line output of Model 4000DS. Playback a 250 Hz "O" VU pre-recorded test tape and measure the output. Then remove the tape and measure the noise level under the same condition. Convert each of the measured values into decibels.

5. TOTAL HARMONIC DISTORTION FACTOR



Fig. 5

Connect the measuring instruments as shown in Fig. 5 and record a 1,000 Hz sine wave signal at "O" VU. Playback the resultant signal and measure the overall distortion factor. Measure the noise level of the tape recorder without the tape. Connect the Audio Frequency Oscillator directly to the distortion meter for measurement of the distortion factor of the oscillator. The required distortion factor can be obtained from the results of the above measurement by the following formula:

$$d_0 = d - d_1 - d_2$$

where, d_0 – Required distortion factor
d – Overall distortion factor
d_1 – Noise level
d_2 – Distortion factor of the oscillator

NOTE: When measuring the distortion factor, new tape should be used.

6. CROSS TALK
(Cross talk between the tracks)



Fig. 6

As shown in Fig. 6, first record a 1,000 Hz sine wave signal on Track No. 3 at +3 VU level. Next, record under a non-input condition. Then, playback the tape on Tracks No. 3 and 4 through the B.P.F. (band pass filter sensitivity ... 1:1) and obtain a ratio between the two from the following formula:

$$C = 20 \log \frac{E_0}{E_2 - E_1} \text{ (dB)}$$

where, C – Desired cross talk ratio (dB)
E_0 – 1,000 Hz signal output level
E_2 – 1,000 Hz cross talk level
E_1 – Non-input signal recorded level

7. ERASE RATIO

As shown in Fig. 4, connect a High Sensitivity V.T.V.M. to the Line Output of Model 4000DS. Playback a virgin tape and take a V.T.V.M. reading of the output level. Next, record a 1,000 Hz sine wave signal at +3 dB, then playback this recorded signal and tape a V.T.V.M. reading of the output level. Next, using this pre-recorded tape, record under a non-input condition and take a reading of the noise level output of the erased signal and obtain a ratio between the two from the following formula:

$$Er = 20 \log \frac{E_0}{E_2 - E_1} \text{ (dB)}$$

Where, Er – Desired erase ratio (dB)
E_0 – 1,000 Hz signal output level
E_2 – Non-input signal recorded level
E_1 – Virgin tape noise output level

III. DISMANTLING OF TAPE TRANSPORT UNIT & AMPLIFIERS

In case of trouble, etc. necessitating disassembly, please disassemble in the order shown in photographs. Reassemble in reverse order.

1

2

3

4



5



6

7

8

MECH. PANEL



9



SCREWS

10



SCREWS

11



MECH. AMP. BLOCK

12



CONNECTION PLUGS CHANGE LEVER

13



14



15



IV. MECHANISM ADJUSTMENTS



Fig. 7



Fig. 8



Fig. 9

1. PINCH WHEEL ADJUSTMENT

It is important that the pinch wheel shaft be kept in perfect alignment with the capstan shaft. Proper pinch wheel pressure is between 1,000 and 1,150 grams when the unit is operated at the tape speed of 7½ ips. Any deviation from this specification will result in wow and flutter. Check pinch wheel pressure with a spring scale, and if necessary, adjust the pinch wheel load spring.

2. SUPPLY REEL SHAFT ASSEMBLY ADJUSTMENT (See Fig. 7 at left)

Felt clutch material (2) is used between the lower side of the reel table base plate (1) and the rewind pulley (3) to protect recording tape from excessive tension during rewind operation. To check the amount of friction of this part, install a 5-inch reel with a 60 mm diameter tape, and gently pull the end of the tape upward with a spring scale. Adjust the conical spring (4) so that the amount of tension is kept between 400 and 500 grams. Other felt clutch material (5) is attached to the supply roller (6) to provide proper slippage during FWD and REC operation. The procedure for checking friction of this part is the same as the foregoing, and between 80 and 100 grams of tension gives best result. Adjust the spring (7) just under the supply roller (6). When the unit is set to fast forward operation, the amount of friction will decrease to from 15 to 20 grams. Check to see whether this is satisfactory. If not, adjust the spring plate (8) and the pressure of the pulley. (9).

3. TAKE-UP REEL SHAFT ASSEMBLY ADJUSTMENT (See Fig. 7 at right)

Felt clutch material (2) is attached to the bottom side of the reel table base plate (1) so that the recording tape will not stretch during fast forward operation due to excessive tension. To check the amount of friction of this part, install a 5-inch reel with a 60 mm diameter tape, and gently pull the end of tape upward with a spring scale. Adjust the conical spring (4) so that the amount of tension at this part is kept between 400 and 500 grams. Other felt clutch material (10) is attached to the take-up roller (11). This is to provide proper slippage during FWD or REC operation. The procedure for checking friction of this part is the same as the foregoing, and between 150 and 180 grams of friction provides the best results. Adjust the spring plate (7) just under the take-up roller (11). When the unit is set to rewind operation, the amount of friction of this part will decrease to from 15 to 20 grams. Check to see whether this is satisfactory. If not, adjust the spring (12) and the pressure of the set sleeve (13).

4. RECORDING/PLAYBACK CHANGING MECHANISM (See Figs. 8, 9)

Turning The FWD/REC knob (N) to recording position causes Lever (a) to pull. Recording Lever (b) (as illustrated by dotted line), and the FWD/REC changing Switch (SW-9) is turned to recording position. If Lever (a) does not pull Lever (b) properly, Changing Switch SW-9 will not operate properly. This may cause abnormal oscillation and inability to record. In this case, loosen Screw (c) and adjust lever.

V. HEAD ADJUSTMENTS



Fig. 10



Fig. 11

Since adjustment of the Heads critically affects tape recorder performance, it is essential that Heads be carefully adjusted with precision measuring equipment and suitable recorded tape.

1. HEAD HEIGHT ADJUSTMENTS (See Figs. 10, 11)

1) Erase Head
Adjust height control screws (a), (b) by turning to left and right so that the upper edge of the tape is 0.15 mm lower than the upper edge of the erase head core.

2) Recording Head
Adjust the screws (c), (d) by turning to left and right until the width between the upper edge of channel 1 head core and upper edge of the tape is equal.

3) Playback Head
Adjust the screws (f), (g) by turning to left and right until the width between the upper edge of channel 1 head core and upper edge of the tape is equal.

2. HEAD SLANT ADJUSTMENT (See Figs. 10, 11)

Adjust the screws (Head Height control screw) by turning to left and right so that each head (Erase, Recording and Playback Head) contacts the tape surface at a right angle.

3. HEAD AZIMUTH ALIGNMENT ADJUSTMENTS (See Figs. 10, 11)

1) Playback Head
Playback an Ampex Alignment test tape (8,000 Hz 3¾ ips.) at 7½ ips. Adjust screw (h) by turning to left and right until the various line outputs are maximum.

2) Recording Head
At recording mode, supply a 15,000 Hz sine wave at a -16 dB recording level an Audio Frequency Oscillator to the line input of the 4000DS, and set the monitor switch to "TAPE" position. Then adjust screw (e) by turning to left and right until the various line outputs are maximum.

4. Repeat adjustments outlined in Items 1-2) to 3, above 2 or 3 times to obtain optimum adjusted condition.

VI. AMPLIFIER ADJUSTMENTS



Fig. 12



Fig. 14



Fig. 13

1. PLAYBACK LEVEL ADJUSTMENT (See Figs. 12, 13, and 14)

1) Set the monitor switch to "TAPE" position and Equalizer switch to 7½ ips.
2) Connect a High Sensitivity V.T.V.M. to the line output.
3) Playback a 250 Hz pre-recorded test tape at 7½ ips., and adjust semi-fixed resistor VR-2 and VR-2b (20 kB) to obtain a 4 dB P.B. level. (VU meter indicates "O" VU)

Recording Amplifier Adjustment should be made only after Head Adjustments and Playback Amplifier Adjustments have been made.

2. RECORDING LEVEL ADJUSTMENT (See Figs. 12, 13, and 14)

1) Set the monitor switch to "TAPE" position and Equalizer switch to 7½ ips.
2) Connect an Audio Frequency Oscillator to the line input and High Sensitivity V.T.V.M. to the line output.
3) Load a Scotch-111 blank tape and set recorder to "REC" mode.
4) Supply a 1,000 Hz sine wave from an Audio Frequency Oscillator and adjust the line recording level control volumes (VR-1 and VR-2 50 kB) until the line output level reaches 4 dB. (VU meter indicates "O" VU)
5) Set the monitor switch to "SOURCE" position.
6) Adjust semi-fixed resistor VR-1 and VR-1b (2 kB) to obtain 4 dB recording level. (VU meter indicates "O" VU)
7) Repeat 2 times in the same way as indicated in Items 4) to 6) above.



Fig. 15



Fig. 16

3. RECORDING BIAS FREQUENCY ADJUSTMENT (See Fig. 16)

1) Set the recorder to recording mode.
2) Connect a Frequency counter to points (A) and (C) in Fig. 16 of the oscillator P.C. Board (LE-5021) and read the frequency indication.
3) If the bias frequency is 105 kHz ±5%, the bias frequency is correct.
4) If the bias frequency is incorrect, it can be adjusted by changing the value of condenser C8 (5600 PF) of the oscillator P.C. Board (LE-5021)

4. RECORDING BIAS VOLTAGE ADJUSTMENT (FREQUENCY RESPONSE ADJUSTMENT) (See Figs. 15, 16)

1) Set the monitor switch to "TAPE" position and equalizer switch to 7½ ips.
2) Connect an Audio Frequency Oscillator to the line input through an Attenuator and a High Sensitivity V.T.V.M. to the line output.
3) Load a blank test tape "AKAI 100L" (Fuji S-100) and set the recorder to "REC" mode.
4) Turn recording level control volume VR-1 and VR-2 (50k A) to obtain 4 dB V.T.V.M. reading.
5) Under conditions described in Item 4) above, readjust attenuator so that the line output level is −16 dB.
6) Record from 40 to 20,000 Hz spot frequencies.
7) Adjust Bias Adjustment semi-fixed condenser C6 (70 PF max.) so that the output of 1,000 Hz and 15,000 Hz frequencies are equal.
8) The bias voltage at this time is around 11V A.C.

5. ERASE VOLTAGE

1) Set the recorder to "REC" mode.
2) Connect a V.T.V.M. to points (B) and (C) in Fig. 16 of the oscillator P.C. Board (LE-5021) and read the V.T.V.M. indication.
3) The Erase Voltage is around 52V A.C.

VII. COMPOSITE VIEWS OF COMPONENTS

PRE-AMP. P.C. BOARD (LE-5022)



OSC. POWER P.C. BOARD (LE-5021)



SECTION 2

PARTS LIST

TABLE OF CONTENTS

HOW TO USE THIS PARTS LIST

1. This parts list is compiled by various individual blocks based on assembly process.
2. When ordering parts, please describe parts number, serial number, and model number in detail.
3. How to read list.



Ref. No.	Parts No.	Description	Schematic No.	Q'ty
		FLYWHEEL BLOCK #13		
12-115x	800425	Flywheel Block Assy. Comp.	RDG#13	1
12-116	244506	Flywheel Only	RD-233	1
12-117x	244754	Felt, Flywheel	RD-275	1
12-118	251324	Main Metal Case	RD-236	1
12-119	253080	Main Metal	RD-237	1

4. The symbol numbers shown on the P.C. Board list can be matched with the Composite Views of components of the Schematic Diagram or Service Manual.
5. The indications of Resistors and Capacitors in the photos of P.C. Board are being eliminated.
6. The shape of the parts and parts name, etc. can be confirmed by comparing them with the parts shown on the Electrical Parts List Table of P.C. Board.
7. Both the kind of part and installation position can be determined by the Parts Number. To determine where a parts number is listed, utilize Parts Index at end of Parts List.
   It is necessary first of all to find the Parts Number. This can be accomplished by using the Reference Number listed at right of parts number in the Parts Index. (meaning of ref. no. outlined in Item 3 above).
8. Utilize separate "Price List for Parts" to determine unit price. The most simple method of finding parts Price is to utilize the reference number.

ELECTRICAL PARTS LIST TABLE

Because the indication of resistors and capacitors in the P. C. Board photos are being eliminated, please confirm parts name and shape by comparing them with the parts shown in this table.

1

Solid Resistor

2 Stopper Type



Insulator Type

Carbon Resistor

3

Metal Oxide Film Resistor

4

Cement Resistor

5

Wire-Wound Resistor

6

Thermistor

7

Enamel Resistor

1

MP Capacitor (Tubler Type)

2

Plastic Capacitor

3

Mylar Capacitor

4

VFM (Hi-Q) Capacitor

5

Mylar Capacitor

6

Tantalum Capacitor

7

Oil Capacitor (Tubler Type)

8 Vertical Type

Tubler Type

Styrol Capacitor

9

Electrolytic Capacitor (Tubler Type)

10 Vertical Type

Tubler Type

Electrolytic Capacitor

11

Ceramic Capacitor

12

Metalized Mylar (Paper) Capacitor

13

Trimmer Condenser

VR

Semi-Fixed Volume

L

Ferri Inductor

TR

Transistor

CR



Spark Quencher

D



Diode (Silicon, Zener, Germanium)

FIG. 1 ILLUSTRATION OF HEAD BLOCK



HEAD BLOCK

Ref. No.	Parts No.	Description	Schematic No.	Q'ty
1-1x	BH480363	Head Block Comp.	LE-1	1
1-2	HZ490296	LD Head Base B (new), w/metal	LD-11	1
1-3	HZ274162	Tape Guide #1	4TR-5	3
1-4	ZW273802	M3 Toothed Lock Washer		3
1-5	ZW273756	M3 Nut		3
1-6	SZ247015	Head Cover Prop	LD-10	2
1-7	ZW417025	Screw, binding head 3x8, w/washer		2
1-8	MH312827	SW. Prop (new LD)	LD-13	1
1-9	ZW417025	Screw, binding head 3x8, w/washer		1
1-10	HZ480420	PB. Angle Base	LE-0001	1
1-11	ZW464714	Screw, round head 3x12		3
1-12	ZG206144	Angle Adjust Spring	RD-16	3
1-13	HP375131	REC./PB. HEAD P4-150		1
1-14x	HZ393974	I-MK Head Terminal Plate	RC-89	1
1-15	ZW477876	Screw, pan head 2x3		2
1-16	HZ480431	Rec. Angle Table	LE-0002	1
1-17	ZW464714	Screw, round head 3x12		3
1-18	ZG206144	Angle Adjust Spring	RD-16	3
1-19	HR475446	REC. HEAD P4-154		1
1-20x	HZ393974	I-MK Head Terminal Plate	RC-89	1
1-21	ZW477876	Screw, pan head 2x3		2
1-22	HZ480442	Erase Head Base	LE-0003	1
1-23	ZW323728	Screw, binding head 3x5		2
1-24	HE384693	ERASE HEAD E4-200		1
1-25	ZW477876	Screw, pan head 2x3		2
1-26	HZ312895	Switch Table (new LD)	LD-12	1
1-27	ES257668	Rotary Switch ESR-E263L14AS	25-6-3	1
1-28	ZW273723	M2 Spring Washer		2
1-29	ZW273734	M2 Nut		2
1-30	EJ255115	Lug Plate VB2L2	33-4-3	1
1-31	EO390622	Ferri Inductor FL9H 220μH(K)	23-1-4	2
1-32	EJ297843	4-P Plug, w/cap	42-1-3	1
1-33	EJ276963	T type 4-P Plug	42-1-16	1
1-34	ZW417025	Screw, binding head 3x8, w/washer		1
1-35	HZ480475	Head Shield	LE-0004	1
1-36	ZW413223	Screw, binding head 3x5, w/washer		2
1-37	HL223503	Shift Lever B, w/shaft A	M9-3	2
1-38	ZG312928	Shifter Spring	LD-19	1
1-39	ZW336846	Washer (SPC)D4.1x7x1.2t		2
1-40	HL312941	Shift Lever, w/pin	LD-15	1
1-41	ZW480622	Screw, oval countersunk head 2.3x6		2
1-42	HL223536	Shift Lever C, w/pin	M9-5	1
1-43	ZW413155	Screw, binding head 3x6		1
1-44	ZW323728	Screw, binding head 3x5		2
1-45	ZW273778	M3 Earth Lug		1

FIG. 2 ILLUSTRATION OF SUPPLY/TAKE-UP REEL TABLE BLOCK



SUPPLY/TAKE-UP REEL TABLE BLOCK

Ref. No.	Parts No.	Description	Schematic No.	Q'ty
2-1x	BR205020	Supply Reel Table Block #5 Comp.	I.E. 1.0	1
2-2x	BR205244	Take-up Reel Table Block #7 Comp.	I.E-1, 1.0	1
2-3	MT256140	Reel Table C, w/shaft C	900-215	2
2-4x	MT252112	Friction Cloth B	900-225	2
2-5	MR251460	Rewind Pulley	900-222	1
2-6	MT222366	Rubber Ring	900-234	1
2-7	ZG227531	Spring G1 (L)	900-229	1
2-8	ZW260054	Washer (SUP)D6.1x10x0.25t		2
2-9x	ZW260065	Washer (SUP)D6.1x10x0.35t		2
2-10	MT255870	Reel Table Thrust Pin	900-237	2
2-11	MR252066	Take-up Roller C	900-220	1
2-12x	MT252101	Friction Cloth A	900-224	1
2-13x	ZW260098	Washer (SUP)D6.1x10x0.5t		2
2-14	MT255971	Reel Table Spring Plate A	900-227	1
2-15	ZW260201	Washer (Nylon)D6.2x13x1t		2
2-16	ZW231693	Claw Thrust Washer (SUP)0.25t	900-235	2
2-17	ZW260201	Washer (Nylon)D6.2x13x1t		2
2-18	MT255870	Reel Table Thrust Pin	900-237	2
2-19	ZW260076	Washer (Nylon)D6.1x10x0.5t		2
2-20	ZW260065	Washer (SUP)D6.1x10x0.35t		4
2-21	MT256228	Reel Metal MT. Parts, w/metal B	900-231	1
2-22	ZW260245	Washer (Nylon)D7.9x13x1t		1
2-23	MT255993	Reel Table Spring Plate C	M8-207	1
2-24	ZW260065	Washer (SUP)D6.1x10x0.35t		1
2-25	ZW270000	Retaining Pin D4	900-257	1
2-26	MR256083	Reel Table Pulley	900-239	1
2-27	ZW434171	Set Screw, hexagon socket 4x7(cup)		1
2-28	MR252044	Take-up Roller A	900-218	1
2-29x	ZG227520	Spring G1(R)	900-229	1
2-30	MR252055	Take-up Roller B	900-219	1
2-31x	MT252123	Friction Cloth C	900-226	1
2-32x	MT255982	Reel Table Spring Plate B	900-228	1
2-33x	MT256228	Reel Metal NT. Parts, w/metal A	900-231	1
2-34	ZW260021	Washer (SUP)D6.1x10x0.13t		1
2-35	ZW312693	'E' Ring 4	6-1-4	1
2-36	ZG227496	Spring F3 (R)	900-238	1
2-37	ZW260201	Washer (Nylon)D6.2x13x1t		2
2-38	MT228587	Set Sleeve	M8-208	1
2-39	ZW434160	Set Screw, hexagon socket 3x3(cup)		1
2-40	MT235596	Vinyl Tube 15		1
2-41	MT480971	Reel Table Disk	I.E.-2001	2
2-42	ZW461305	Screw, countersunk head 3x5(black)		2

FIG. 3 ILLUSTRATION OF MOTOR BLOCK



MOTOR BLOCK

Ref. No.	Parts No.	Description	Schematic No.	Q'ty
3-1x	BM271800	Motor Block Comp.	LE-1, LD	1
3-2	MZ395144	900 Motor Cover B, w/metal	900-709	1
3-3	UC254250	Motor Bottom Plate	900-721	1
3-4x	ZW384131	Screw, round head 3x5		2
3-5x	MZ257591	Rotor Fan	3A-758	2
3-6x	MV269965	Ball D4		1
3-7	MZ395166	900 Motor Cover A, w/metal	900-707	1
3-8x	ZW260245	Washer (Nylon)D7.9x13x1t		1
3-9x	MZ253956	Motor Oil Cap D	900-725	1
3-10x	EZ335204	Felt D14x19x4t	900-744	1
3-11	ZW427037	Screw, pan head 4x50, w/washer		4
3-12	ZW254621	Motor Hexagon Nut	900-737	4
3-13	MZ254351	Motor Mt. plate A	900-738	1
3-14	MZ254160	Motor Prop A	24X-730	2
3-15	MZ254182	Motor Prop B	24X-731	1
3-16	ZW424056	Screw, pan head 4x10		5
3-17	MR254496	Motor Pulley	SRA-5	1
3-18	MR300644	900 Type Knurled Pulley	900-735	1
3-19	ZW300655	900 Type Knurled Pulley Set Screw	900-736	1
3-20	MZ292364	XR Motor Shield Plate B	XR-705	1
3-21	MB254158	Motor Shield Setting Band	LD-701	1
3-22	ZW424056	Screw, pan head 4x10		1
3-23x	ZW413188	M4 Nut		1
3-24	ZW272395	M7 Motor Prop Set Screw	24X-732	1
3-25	ZW200474	Screw, countersunk head 4x10		2
3-26	EC410016	MP/C. 2+0.5μF 300VAC (Lug type Uni/D.)	24-9-13	1
3-27x	EC273442	MP/C. 2μF 250WVAC (Lug type Op./D.) (AAL,CSA)	24-9-20	1
3-28	ER339805	Cement/R. H20B 450Ω(K) (Wire-wound type), w/belt	35-16-16	1
3-29	ZW413223	Screw, binding head 3x5 w/washer		1

FIG. 4 ILLUSTRATION OF FLYWHEEL/ BELT CHANGE LEVER BLOCK



FLYWHEEL/BELT CHANGE LEVER BLOCK

Ref. No.	Parts No.	Description	Schematic No.	Q'ty
		FLYWHEEL BLOCK		
4-1x	BF205075	Flywheel Block #5 Comp.		1
4-2	MZ244473	Flywheel	707-S-10	1
4-3	MS244708	Flywheel Shaft	SRA-21	1
4-4	ZW373577	Set Screw, hexagon socket 5x6(flat)		2
4-5	ZW447208	Flywheel Thrust B D7.9x13x0.5t	101025	1
4-6	MZ296267	Main Case B 24 Comp.	1630-205	1
4-7	MZ446635	Thrust Cap, Main Metal B2	LF-2006	1
4-8	ZW244710	Flywheel Fixing Pin	900-250	1
4-9x	MZ244113	Felt D12.5x16x2t		1
4-10	MZ253113	Main Metal Cap B	MH-208	1
4-11	MY270055	Capstan D8	SRA-7	1
4-12	ZW293027	1100 Capstan Screw	SRA-6R	1
4-13x	BC252977	Main Shaft Collar	SRA-32	1
		BELT CHANGE LEVER BLOCK		
4-14x	BL203523	Belt Change Lever Block Comp.	A	1
4-15	ML217451	Belt Change Lever (small), w/roller B	MH-221	1
4-16	MZ248354	Belt Guide Stop, w/metal	4TR-221	1
4-17	ZG217337	Belt Return Spring	4TR-224	1
4-18	ZW413201	Screw, pan head 4x8		1
4-19x	ZG217394	Belt Change Spring B	MH-125	1
4-20x	ZW260054	Washer (SUP)D6.1x10x0.25t		1
4-21x	ZW290283	'U' Ring 2.85M	6-1-1	1
				1
4-22	MB256601	Double Face Flat Belt D=110	100912	1
4-23	MZ244631	Flywheel Prop B	4TR-115	1
4-24	MZ244620	Flywheel Prop A	4TR-116	1
4-25x	ZW424056	Screw, pan head 4x10		2
4-26x	ZW273914	M4 Spring Washer		2
4-27	ZW244574	Flywheel Support Adjust Screw	4TR-114	1
4-28x	ZW231794	Tape Guide Washer (small)	3A-355	1
4-29	ZW274048	M5 Nut		1
4-30	MZ244530	Flywheel Support Plate B	M8-109	1
4-31	ZW235585	Nylon Plate D=8		1
4-32	ZW413998	Washer (SPC)D6.8x12.7x1t		1
4-33	ZW393232	1/4 Inch Spring Washer		1
4-34	ZW413280	Inch Nut 1/4 Thread=20		1
4-35	MV269965	Steel Ball 4mm		1

FIG. 5 ILLUSTRATION OF SWITCH BLOCK



SWITCH BLOCK

Ref. No.	Parts No.	Description	Schematic No.	Q'ty
S-1x	BS480352	Switch Block Comp.	I.L.	1
S-2	MZ316901	Switch Table A-2 (SX), w/prop	MR-201	1
S-3	ES316934	Y Type RWD Shaft	25-8-5	1
S-4	ES369865	RCC Y Type RWD Shaft	RCC-202	1
S-5x	MZ316945	Nut Plate	MR-245	2
S-6x	ZW202138	Screw, binding head 3x6, w/washer		4
S-7x	MZ316956	Cam A-3	MR-242	1
S-8x	ZW413201	Screw, pan head 4x8		1
S-9x	ZW260133	Washer (Fiber)D6.1x10x1t		2
S-10	MZ327341	Cam Trap Plate B	SX-201	1
S-11	ZG227586	Spring K	900-214	1
S-12	MZ327352	Cam C-2	SX-202	1
S-13	ZW201778	Screw, pan head 4x8		1
S-14x	ZW434215	Washer (Nylon) D6.1x10.3x0.3t		1
S-15x	ZW434193	Washer (Nylon) D6.1x10.3x0.5t		1
S-16x	MV270066	Steel Ball D8		1
S-17x	MZ217293	Cam B-2, without tap	1630-201	1
S-18x	ZW416687	Screw, binding head 4x8		1
S-19	ML257128	Lever I, w/shaft	900-209	1
S-20	MZ217203	Cam Roller A	900-153	1
S-21x	ZW290283	'U' Ring 2.85M	6-1-1	1
S-22	ZW217877	Pause Lever Set Screw	900-136	1
S-23x	ZW260166	Washer (Nylon) D6.2x13x0.125t		1
S-24x	ZW273892	M4 Toothed Lock Washer		1
S-25	ZW273960	M4 Nut		1
S-26	MZ225720	Switch Table B-2	M9-308	1
S-27	ZW413201	Screw, pan head 4x8		2
S-28	MZ258581	Rec. Lever Prop	M9-303	1
S-29	ZW260133	Washer (Fiber)D6.1x10x1t		1
S-30	MZ317068	Amp. Switch Cam B	MR-243	1
S-31	ZW413201	Screw, pan head 4x8		1
S-32	MZ217686	Pause Lever Cushion	LL-102	1
S-33	ML488744	Rec. Lever C, w/shaft B	LL-2002	1
S-34	MR269728	Cam Roller D12.5	RC-126	1
S-35x	ZW290283	'U' Ring 2.85M	6-1-1	1
S-36	ML226146	Switch Lever BL	LD-103	1
S-37	ZW203253	Hexagon Bolt 4x7, w/washer		2
S-38	ZG227564	Spring H	900-120	1
S-39	ZW290283	'U' Ring 2.85M	6-1-1	1
S-40	ZG227485	Spring E	900-119	1

FIG. 6 ILLUSTRATION OF MECHANISM ASSEMBLY BLOCK



MECHANISM ASSEMBLY BLOCK

Ref. No.	Parts No.	Description	Schematic No.	Q'ty
		TAPE GUIDE BLOCK	LE, LF DF, LS	
6-1x	BZ400948	Tape Guide Block #4 Comp	AT-16	1
6-2	MZ204311	Tape Guide Prop #1700	LC-618	1
6-3	SZ465377	Tape Guide Talbe A		1
6-4	ZW231805	Tape Guide Washer (large) (SUS27)0.5t	3A-356	2
6-5	MV248117	Bearing 635AHZZ-CIE-B32		1
6-6	SZ465388	Tape Guide Table B	LC-619	1
		MECHANISM ASSEMBLY BLOCK		
6-7	MZ271776	Mech. Frame LD, w/bush	LD-101	1
6-8	MZ273295	M-9 Mech. Panel Prop	M9-302	4
6-9x	ZW414033	Screw, countersunk head 3x8		4
6-10	MS257051	Lever FA Shaft	900-127	1
6-11x	ZW413267	Flange Nut M4		1
6-12	HZ247511	Head Prop C	900-142	2
6-13x	ZW413201	Screw, pan head 4x8		2
6-14x	ZW414044	Screw, countersunk head 4x8		1
6-15x	MH258816	Hexagon Head Prop	LD-102	1
6-16x	MZ410938	Belt Guide Pin	LF-1009	1
6-17x	ZW413188	M4 Nut		3
6-18	MZ257073	Lever FB Guide Base	M9-103	1
6-19x	ZW417150	Screw, pan head 4x6		2
6-20	ZG257095	Lever FB Vibration Proof Spring	M8-104	1
6-21	MS245463	Brake Lever Shaft	900-129	2
6-22x	MZ245485	Brake Lever Pin (AAL,CSA)	MH-138	1
6-23	MZ312524	Shifter Cam	LD-106	1
6-24	MZ312535	Shifter Cam Collar	LD-107	1
6-25	ZW393726	Screw, truss head 3x10		1
6-26	ES250007	Micro Switch M-8-3 U/L	25-1-6	1
6-27	MZ373961	Micro Switch Prop	RCC-129	2
6-28	MZ205817	Actuator JW-560	21-1-5	1
6-29x	ZW414055	Screw, binding head 3x30		1
6-30	ZW414066	Screw, binding head 3x25		1
6-31x	ZW273756	M3 Nut		1
6-32x	ZW273802	M3 Toothed Lock Washer		1
6-33x	ER376435	Spark Quencher U/L 0.1μ+120 250WV(CEE)	41-1-35	1
6-34x	ML308564	Belt Vibration Stopper (AAL,CSA)	MH-137	1
6-35x	ZW413188	M4 Nut		2
6-36x	MZ452496	Cycle Angle (CEE)	LS-1007	1
6-37x	ZW413201	Screw, pan head 4x8		1
6-38x	ZW330412	Adjust Washer (U) (PBP)D4x13x0.13t		1
6-39x	ZW330423	Adjust Washer (U) (SUP)D4x13x0.25t		1
6-40x	ZW330434	Adjust Wasehr (U) (SUP)D4x13x0.5t		1
6-41x	ZW330445	Adjust Washer (U) (SUP)D4x13x0.8t		1
6-42x	ZW273881	M4 Earth Lug		1
6-43x	ZW413267	Flange Nut M4		3
6-44x	ZW462835	Washer (PBP)D4.3x11x0.2t		1
6-45x	ZW462846	Washer (PBP)D4.3x11x0.3t		1
6-46	ML475920	New Spring Hook	900-185	1
6-47x	ZW323728	Screw, binding head 3x5		1
6-48	MS260515	A Lever Shaft	900-126	1
6-49	ML309093	Lever B, w/lever D	900-103	1
6-50	MZ217203	Cam Roller A	900-153	2
6-51	ZG469427	Spring B-1	LS-2004	1
6-52	MZ253653	Metal Mt. Part,w/metal	900-174	1
6-53	ML270685	G Lever, w/lever HB	900-109	1
6-54	MS205558	Idler Shaft A	900-124	1
6-55	MZ217708	Pause Lever Retaining Metal B	900-170	1
6-56	ZG227575	Spring I	900-121	1
6-57x	MZ256814	Rewind Shaft Spacer	M9-124	2
6-58x	ZW202105	Screw, binding head 3x5, w/lug plate		1
6-59	ZG208091	Impedance Arm Spring	RD-269	1
6-60	ZG312748	Shifter Spoke	LD-105	1
6-61	MZ293567	Head Lifter Cam A #1630	1630-104	1
6-62	MZ293578	Head Lifter Cam B #1630	1630-105	1
6-63x	ZW413223	Screw, binding head 3x5, w/washer		1
6-64	ML217934	Supply Brake Comp.	900-113	1
6-65	ML251932	Take-up Brake Comp.	900-114	1
6-66x	ZW259942	Washer (Fiber) D5.1x10.3x0.5t		3
6-67	ZW290283	'U' Ring 2.85M	6-1-1	3
6-68	ML300161	707 Lever A, w/metal	LC-103	1
6-69	ML257196	Lever LC, w/lever E2	LC-308	1
6-70x	ZW201767	Screw, pan head 4x6, w/washer		2
6-71	ZW259918	Washer (presspan) D5.1x10.3x0.25t		4
6-72	ZW290283	'U' Ring 2.85M	6-1-1	3
6-73	ZG290384	UN Spring D	1630-108	1
6-74	ML256983	Lever C2	900-104	1
6-75	ZG227452	Spring D	900-118	1
6-76	ZG227441	Spring C	900-117	1
6-77	MZ260662	AS Lever Prod Base, w/prop	4TR-236	1
6-78	ZW323728	Screw, binding head 3x5		2
6-79	ZW273767	Earth Lug D3x20L		1
6-80	ML257040	Lever FA	900-107	1
6-81	MZ217203	Cam Roller A	900-153	1
6-82x	ZW290283	'U' Ring 2.85M	6-1-1	1
6-83	ML295727	2 Speed Motor Lever F, w/shaft	M8-107	1
6-84	ZG270358	F.B Pull Spring	M8-108	1
6-85	ML257163	Lever K, w/shaft	900-111	1
6-86	ZW260166	Washer (Nylon) D6.2x13x0.125t		2
6-87	ZW223233	Fulcrum Screw A	900-135	1
6-88	ZG227575	Spring I	900-121	1
6-89	ML243540	Pinch Roller Lever	900-161	1
6-90	MS243404	Pinch Roller Shaft C	4TR-102	1
6-91x	ZW259975	Washer (SUP)D5.1x10.3x0.8t		1
6-92	ZW413188	M4 Nut		1
6-93	MR269763	Cam Roller D13	900-154	1
6-94	MS217192	Cam Roller Shaft A	900-130	1
6-95	ZG227417	Spring A	900-115	1
6-96x	ZW376391	Washer (Polyslider) D6.1x10x0.13t		1
6-97	ML479957	Pause Lever (LE), w/screw	LE-1001	1
6-98	ZW217877	Pause Lever Set Screw	900-138	1
6-99	MZ217855	Pause Stopper	900-169	1
6-100	ZW323728	Screw, binding head 3x5		1
6-101	ZG217866	Pause Lever Spring A	900-123	1
6-102x	ZW259795	Washer (SUP)D4.3x11x0.13t		1
6-103	MZ217686	Pause Lever Cushion	LC-102	1
6-104	MZ217113	Cam Stopper B	RC-129	1
6-105	ZW217102	Cam Stopper Insulator Holder	900-165	1
6-106	ZW413245	Screw, pan head 4x15		2
6-107x	ZW413188	M4 Nut		2
6-108	SB488698	Rec. Button	900-167	1
6-109x	ZW318532	Cotter Pin 1x6		1
6-110	MC479968	Counter MP491-28	9-1-23	1
6-111x	MB406168	Counter Belt D123x1.8	3H-3296	1
6-112	BL204658	AS Lever Block #2 Comp.		1
6-113x	ZW322525	Washer (PBP)D4.1x7x0.2t		1
6-114	ZW290294	'U' Ring 2.85M	6-1-1B	1
6-115x	MP204794	Pinch Roller #3	3A-348	1
6-116	MI204423	Idler Wheel #2		2
6-117x	ZW260076	Washer (Nylon)D6.1x10x0.5t		3
6-118x	ZW376391	Washer (Polyslider) D6.1x10x0.13t		2
6-119	ZW290283	'U' Ring 2.85M	6-1-1	3
6-120	MI231423	Middle Wheel, w/metal	900-155	1
6-121	ZW260122	Washer (Nylon)D6.1x10x1t		1
6-122x	EJ317125	SP TV-Consent-Plug	42-1-6	1
6-123x	MZ396393	Lock Wire Tie 11M/M		1
6-124x	EJ205975	Cramp Terminal 1-SD	22-1-7	3
6-125	ML226258	Start Lever A, w/lever B-2	4TR-122	1
6-126	SB425777	Start Button	MS-1002	1
6-127x	ZW314728	Cotter Pin 1.6x8		1
6-128x	ZW425788	Screw, round head 3x4		2
6-129	ZG217394	Belt Change Spring B	MH-135	1
6-130	MZ316956	Cam A-3	MR-242	1
6-131	MZ217293	Cam B-2, without Tap	1630-201	1
6-132	ZM416687	Screw, binding head 4x8		2
6-133	MV270066	Steel Ball D=8		1

FIG. 7 PHOTO OF PRE-AMP. P.C. BOARD (LE-5022)



PRE-AMP. P.C. BOARD (LE-5022) BLOCK

Symbol No.	Parts No.	Description	Q'ty
7-1x	BA480251	Pre-Amp. P.C. Board Comp. (LE-5022)	1
7-IC1,2	EI412413	Line Amp. I.C. LD-3141	4
7-TR1	ET352146	Transistor 2SC458LG(D)	2
7-TR2	ET398845	Transistor 2SC871(E,F)	2
7-TR3,4	ET234854	Transistor 2SC458LG(C)	4
7-D1	ED219464	Germanium Diode 1N34A	2
7-VR1	EV337577	Semi-fixed Volume V10K5-2-4 2k B	2
7-VR2	EV337588	Semi-fixed Volume V10K5-2-4 20k B	2
7-L1	EO243977	Ferri Inductor FL7H 1MH(J)	2
7-L2	EO244001	Ferri Inductor FL9H 10MH(J)	2
7-T1	BT247746	Head Phone Trans. N19-228S	2
		Capacitor, Vertical Type	
7-C1	EC432810	Elect. 10μF 16WV(noiseless)	2
7-C2	EC290520	VFM 100PF(J) 50WV	2
7-C3	EC220364	Elect. 100μF 6.3WV	2
7-C4	EC493323	Elect. 1μF 25WV(noiseless)	2
7-C5	EC476965	Elect. 47μF 25WV(noiseless)	2
7-C6	EC220678	Elect. 47μF 25WV	2
7-C7	EC290520	VFM 100PF(J) 50WV	2
7-C8	EC320051	Elect. 10μF 16WV	2
7-C9	EC220364	Elect. 100μF 6.3WV	2
7-C10	EC446297	Mylar 0.18μF(J) 50WV	2
7-C11	MC220364	Elect. 100μF 6.3WV	2
7-C12	EC368335	Mylar 0.022μF(J) 50WV	2
7-C13	EC220994	Elect. 10μF 25WV	2
7-C14	EC320051	Elect. 10μF 16WV	2
7-C15	EC368335	Mylar 0.022μF(J) 50WV	2
7-C16	EC423562	VFM 470PF(J) 50WV	2
7-C17	EC450527	Elect. 4.7μF 25WV	2
7-C18	EC336216	VFM 330PF(J) 50WV	2
7-C19	EC480071	Elect. 22μF 16WV(noiseless)	2
7-C20	EC336216	VFM 330PF(J) 50WV	2
7-C21	EC476965	Elect. 47μF 25WV(noiseless)	2
7-C22	EC329771	Elect. 47μF 6.3WV	2
7-C23	EC379170	Mylar 0.1μF(J) 50WV	2
7-C24	EC379787	Mylar 0.0039μF(J) 50WV	2
7-C25	EC389485	Mylar 0.018μF(J) 50WV	2
7-C26	EC290520	VFM 100PF(J) 50WV	2
7-C27	EC329771	Elect. 47μF 6.3WV	2
7-C28	EC450527	Elect. 4.7μF 25WV	2
7-C29	EC220678	Elect. 47μF 25WV	2
7-C30	EC450527	Elect. 4.7μF 25WV	2
7-C31	EC329850	VFM 220PF(J) 50WV	2
7-C32	EC329771	Elect. 47μF 6.3WV	2
7-C33	EC220364	Elect. 100μF 6.3WV	2
7-C34	EC329850	VFM 220PF(J) 50WV	2
7-C35	EC350684	Elect. 22μF 25WV	2
7-C36	EC320051	Elect. 10μF 16WV	2
		Resistor, Stopper Type	
7-R1	ER349907	Carbon RD1/4 33k(J)	2
7-R2	ER414303	Carbon RD1/4 220k(J) (noiseless)	2
7-R3	ER306360	Carbon RD1/4 6.8k(J)	2
7-R4	ER480060	Carbon RD1/4 33k(J) (noiseless)	2
7-R5	ER211465	Carbon RD1/4 1k(J)	2
7-R6	ER213030	Carbon RD1/4 5.6k(J)	2
7-R7	ER346601	Carbon RD1/4 47k(J)	2
7-R8	ER212883	Carbon RD1/4 4.7k(J)	2
7-R9	ER346601	Carbon RD1/4 47k(J)	2
7-R10	ER380711	Carbon RD1/4 220k(J)	2
7-R11	ER346994	Carbon RD1/4 18k(J)	2
7-R12	ER336442	Carbon RD1/4 10k(J)	2
7-R13	ER212264	Carbon RD1/4 22k(J)	2
7-R14	ER336442	Carbon RD1/4 10k(J)	2
7-R15	ER342933	Carbon RD1/4 27k(J)	2
7-R16	ER363644	Carbon RD1/4 560(J)	2
7-R17	ER213300	Carbon RD1/4 680(J)	2
7-R18	ER306843	Carbon RD1/4 1.2k(J)	2
7-R19	ER336442	Carbon RD1/4 10k(J)	2
7-R20	ER362485	Carbon RD1/4 330k(J)	2
7-R21	ER212681	Carbon RD1/4 330(J)	2
7-R22	ER347038	Carbon RD1/4 270(J)	2
7-R23	ER450011	Carbon RD1/4 120k(J)	2
7-R24	ER343078	Carbon RD1/4 2.7k(J)	2
7-R25,26	ER336442	Carbon RD1/4 10k(J)	4
7-R27	ER357570	Carbon RD1/4 150k(J)	2
7-R28	ER212883	Carbon RD1/4 4.7k(J)	2
7-R29	ER212477	Carbon RD1/4 3.3k(J)	2
7-R30,31	ER212264	Carbon RD1/4 22k(J)	4
7-R32	ER212883	Carbon RD1/4 4.7k(J)	2
7-R33	ER343078	Carbon RD1/4 2.7k(J)	2

When ordering parts, please describe Parts Number, Serial Number, and Model Number in detail.

FIG. 8 PHOTO OF OSC. POWER P.C. BOARD (LE-5021)



OSC. POWER P.C. BOARD (LE-5021) BLOCK

Symbol No.	Parts No.	Description	Q'ty
8-1x	BA480306	OSC. Power P.C. Board Comp. (LE-5021)	1
8-2	EZ480396	Heat-sink Plate	1
8-TR1	ET476886	Transistor 2SC1098(L,M)	1
8-3	ZW413155	Screw, binding head 3x6	3
8-TR2,3	ET304255	Transistor 2SC971(2,3) (red)	2
8-D1	ED329130	Silicon Diode 10DC-1(black)	1
8-D2	ED377234	Zener Diode 1S339-A	1
8-T1	EO383365	OSC. Coil OT-204	1
8-L1,2	EO321254	Ferri Inductor FL7H 5.6MH(J)	2
8-4	EZ480418	Socket Table	1
8-5	EJ374027	4P Socket	1
8-6x	ZW447772	Tapping Screw 3x6(BR)	2
		Capacitor, Vertical Type	
8-C1,2	EC337533	Elect. 220μF 50WV	2
8-C3	EC313121	Elect. 220μF 25WV	1
8-C4,5	EC350717	VFM 390PF(J) 50WV	2
8-C6,7	EC425250	Trimmer A-1P3-3 70PF	2
8-C8	EC383400	Plustic Film 5600PF(J) 500WV	1
8-C9	EC220678	Elect. 47μF 25WV	1
8-C10,11	EC250841	Mylar 0.01μF(J) 50WV	2
8-C12	EC350875	Mylar 0.001μF(J) 50WV	1
8-C13	EC250841	Mylar 0.01μF(J) 50WV	1
		Resistor, Stopper Type	
8-R1	ER212883	Carbon RD1/4 4.7k(J)	1
8-R2	ER361642	Carbon RD1/4 47(J)	1
8-R3	ER413717	Wire-wound 3WL 18(J) (L type)	1
8-R4	ER398856	Metal Oxide Film 1W 100(K)	1
8-R5	ER212883	Carbon RD1/4 4.7k(J)	1
8-R6	ER304402	Carbon RD1/4 470(J)	1
8-R7,8	ER315944	Carbon RD1/4 3.3(J)	2

FIG. 9 PHOTO OF AMP. ASSEMBLY BLOCK





AMP. ASSEMBLY BLOCK

Ref. No.	Parts No.	Description	Schematic No.	Q'ty
	POWER SUPPLY FRAME BLOCK			
9-1x	BZ480262	Power Supply Frame Block Comp.	LE	1
9-2x	BZ480273	Power Supply Frame Block Comp. (AAL)	LE	1
9-3x	BZ480284	Power Supply Frame Block Comp. (CSA)	LE	1
9-4x	BZ480295	Power Supply Frame Block Comp. (CEE)	LE	1
9-5	EZ479992	Power Supply Frame A	LE-5009	1
9-6x	EZ480003	Power Supply Frame B (AAL, CSA, CEE)	LE-5009	1
9-7	BT480014	Power Trans. LET-1	38-4-162	1
9-8x	BT480025	Power Trans. LET-2 (AAL)	38-4-163	1
9-9x	BT480036	Power Trans. LET-3 (CSA)	38-4-160	1
9-10x	BT480047	Power Trans. LET-4 (CEE)	38-4-161	1
9-11	EZ481296	Trans. Shield (LE)	LE-5034	1
9-12x	ZW323728	Screw, binding head 3x5		1
9-13x	ZW273756	M3 Nut		1
9-14x	ZW434250	Screw, pan head 4x8, w/washer		2
9-15x	ZW273914	M4 Spring Washer		2
9-16	ZW413188	M4 Nut		2
9-17	EJ277108	5P TV-Consent-Socket	31-1-19	1
9-18x	ZW447772	Tapping Screw 3x6(BR)		2
9-19	EZ480824	REC. Switch Holder	LE-5013	1
9-20	ES317744	Slide Switch SL-242B4V	25-3-28	1
9-21x	ZW461935	Screw, round head 2.6x4		2
9-22	ZG227428	Spring B	900-116	1
9-23x	ZW273881	M4 Earth Lug		2
9-24x	EZ493277	Rec. Switch Return Lever	LE-5036	1
9-25x	ZW207314	Amp. Lever Set Screw	3A-737	2
9-26x	ZW447772	Tapping Screw 3x6(BR)		6
9-27	EZ480846	Power Switch Table	LE-5011	1
9-28	ES480857	Seesaw Switch JA-07 TV-3	25-2-29	1
9-29x	ES480868	Seesaw Switch JA-04 250V 5A (CEE)	25-2-31	1
9-30	ZW323728	Screw, binding head 3x5		2
9-31	ER376413	Spark Quencher U/L 0.033μ+120 500WV	48-1-37	1
9-32	ZW447772	Tapping Screw 3x6(BR)		2
9-33	EJ233370	Socket (Volt. Selector) S-18010	40-2-3	1
9-34	ZW379405	Iso Screw, binding head 3x6		2
9-35	ES375478	Slide Switch ESD-279DU	25-3-23	1
9-36	EZ223817	Frequency Change Name Plate	3A-741	1
9-37	ZW371856	Iso Screw, binding head 3x5		2
9-38x	EF277424	Fuse ST-4 0.8A	39-1-28	1
9-39x	EF238634	Fuse 400MAT(T type) (CEE)		1
9-40x	EF375647	Fuse 500MAT(T type) (CEE)		2
9-41x	EJ254970	Lug Plate KP1L1 (AAL)	33-3-3	1
9-42x	EJ480914	Fuse Holder (CEE)	101060	1
9-43x	EA480925	Fuse Terminal Plate 1 (CSA)	101061	1
9-44	EZ382263	Strain Relief SR-4K-4	2-7-12	1
9-45x	EZ246936	Strain Relief SR-6W-1 (3 core)	2-7-8	1
9-46	EZ374894	U/L AC Cord 3M	26-3-19	1
9-47x	EZ315448	Australia Cord	26-3-11	1
9-48x	EZ354240	Power Cord ER0150 (CEE)		1
9-49	BA480306	OSC. Power P.C. Board Comp. (LE-5021)		1
9-50x	ZW413223	Screw, binding head 3x5 w/washer		4
9-51x	MB259233	Wire Band C	3A-745	1
9-52	EJ205975	Cramp Terminal 1-SD	32-1-7	2
	CONTROL CHASSIS BLOCK			
9-53x	BZ480317	Control Chassis Block Comp.	LE	1
9-54	EZ480521	Control Chassis	LE-5015	1
9-55	EZ480532	Head Phone Jack Plate	LE-5017	1
9-56x	ZW447772	Tapping Screw 3x6(BR)		2
9-57	EJ437321	3-P Molded-Jack 3PMJ1P	31-2-38	1
9-58	ZW272722	M9 Toothed Washer D9.3x13x0.5t		1
9-59x	ZW454860	Washer (Fiber)D9.2x15x0.5t		1
9-60	ZW391680	E Jack Nut	7-1-20	1
9-61	ES480543	Seesaw Switch 2 Circuit 2 Contactor	25-2-27	3
9-62	ES480554	Seesaw Switch 4 Contactor Earth type	26-2-26	1
9-63	ZW447772	Tapping Screw 3x6(BR)		8
9-64	EV480565	Double Volume DJ10A 50k Ax2	36-3-41	2
9-65	EA480576	Lamp P.C. Board	LE-5018	1
9-66x	EL338196	No. 2 Lamp 8V 0.2A	28-2-9	1
9-67x	ER345712	Carbon RD1/4 22k(J)	35-9-5	1
9-68x	ZW273778	M3 Earth Lug		2
9-69x	EC379192	Mylar/C. 0.039μF(J) 50WV	24-1-1	4
9-70x	EC379157	Mylar/C. 0.003μF(J) 50WV	24-1-1	2
9-71	EZ480587	Mech. Panel Table	LE-5016	2
9-72x	ZW447772	Tapping Screw 3x6(BR)		8
	JACK PLATE BLOCK			
9-73x	BZ480240	Jack Plate Block Comp.	LE-1	1
9-74x	BZ486832	Jack Plate Block Comp. (CEE)	LE-1	1
9-75	EZ480497	Jack Base	LE-5003	1
9-76	EJ480508	Jack Plate, w/jack	LE-5004	1
9-77	ZW201183	Screw, truss head 3x8 (black)		4
9-78x	ZW273756	M3 Nut		4
9-79x	ER213873	Carbon/R. RD1/4 150k(J) (Insu. type)	35-9-5	2
9-80x	ER324685	Carbon/R. RD1/4 33k(J) (Insu. type)	35-9-5	2
9-81x	ER440921	Carbon/R. RD1/4 27k(J) (Insu. type) (CEE)	35-9-5	2
9-82x	ER214290	Carbon/R. RD1/4 4.7k(J) (Insu. type)	35-9-5	2
9-83x	ER213647	Carbon/R. RD1/4 10k(J) (Insu. type) (CEE)	35-9-5	2
9-84x	ER345712	Carbon/R. RD1/4 22k(J) (Insu. type)	35-9-5	4
	AMP. CHASSIS BLOCK			
9-85x	BZ480238	Amp. Chassis Block Comp.	LE-1	1
9-86x	BZ486843	Amp. Chassis Block Comp. (CEE)	LE-1	1
9-87	EZ480598	Amp. Chassis	LE-5001	1
9-88x	EZ480600	P.C. Board Angle	LE-5006	1
9-89	EJ298607	4P Jack	31-1-10	1
9-90x	ZW273881	M4 Earth Lug		1
9-91	EZ488957	Mic. Jack Table	LE-5206	1
9-92	EJ374016	Mic. Jack 2PMJ1	31-2-23	2
9-93x	EZ225180	Nylon Collar, Jack	LE-520	2
9-94x	ZW455275	Washer (Fiber)D9.1x18x0.5t		2
9-95	ZW391680	E Jack Nut	7-1-20	2
9-96x	ZW447772	Tapping Screw 3x6(BR)		8
9-97x	BZ480240	Jack Plate Block Comp.	LE-1	1
9-98x	BZ486832	Jack Plate Block Comp. (CEE)	LE-1	1
9-99	ZW447772	Tapping Screw 3x6(BR)		4
9-100x	MB259233	Wire Band C	3A-745	1
	AMP. ASSEMBLY BLOCK			
9-101	BA480251	Pre-Amp. P.C. Board Comp. (LE-5022)		1
9-102	EZ314504	Shield Plate Prop	MR-525	3
9-103	EZ480756	Shield Plate	LE-5006	1
9-104x	ZW273756	M3 Nut		3
9-105	EZ480982	Sash Angle A (left)	LE-6046	1
9-106	EZ480993	Sash Angle B (right)	LE-6048	1
9-107	ZW447772	Tapping Screw 3x6(BR)		14
9-108x	EZ480767	LE Pre-Amp. Harness	26-6-95	1
9-109	EZ225303	Upper Angle	LE-508	1
9-110	EM480778	VU Meter B1914R	36-1-57	2
9-111	EZ480780	Lamp Mask	LE-5023	1
9-112x	EZ486865	Lamp Mask B	LE-5035	2
9-113	ZW290248	'U' type Speed Nut M4 #1(small)	6-3-1	4
9-114	ZW290250	'U' type Speed Nut M4 #1(large)	6-3-2	6
9-115	SL493042	Rec. Wire B	LE-6028	1

FIG. 10 PHOTO OF FINAL ASSEMBLY BLOCK

FINAL ASSEMBLY BLOCK

Ref. No.	Parts No.	Description	Schematic No.	Q'ty
		MECH. PANEL BLOCK		
10-1x	BZ480172	Mech. Panel Block Comp.	LE	1
10-2x	BZ480183	Mech. Panel Block Comp. (CSA,AAL)	LE	1
10-3x	BZ486854	Mech. Panel Block Comp. (CEE)	LE	1
10-4	SP480723	Mech. Panel A	LE-6001	1
10-5x	SP480734	Mech. Panel B (CSA,AAL)	LE-6001	1
10-6x	SP485730	Mech. Panel C (CEE)	LE-6001	1
10-7	SM480745	Reel Table Ring	LE-6003	2
10-8	SZ276816	ST-1 Capstan Rest	100180	1
10-9x	ZW424124	Screw, countersunk head 3x5		1
10-10	SZ330895	MR Counter Escutcheon	MR-646	1
		CASE BLOCK		
10-11	BC480161	Case Block Comp.	LE-1	1
10-12	SZ482152	LE Case Foot	LE-4002	2
10-13x	ZW419646	Washer (SPC)D4.5x9.8x0.5t		4
10-14x	ZW413188	M4 Nut		4
10-15x	SZ382217	Fan Grill	RD-A402	1
10-16x	ZW324448	Tapping Screw #1 3x10(truss)		3
10-17	SZ480712	Dust Cover Pin	LE-6024	2
		FINAL ASSEMBLY BLOCK		
10-18x	ZW200643	Tapping Screw #1 4x25(truss)		2
10-19x	SZ377190	LM Rubber Foot	LM-404	4
10-20x	ZW419646	Washer (SPC)D4.5x9.8x0.5t		4
10-21x	ZW434283	Tapping Screw #1 4x30(truss)		4
10-22	ZW467853	Screw, truss head 3x6, w/washer		4
10-23x	ZW413155	Screw, binding head 3x6		2
10-24	SP481004	Sash	LE-6009	2
10-25x	ZW424124	Screw, countersunk head 3x5		6
10-26	SP481015	Amp. Panel	LE-6006	1
10-27	EZ426780	Illumination Escutcheon(red)	61-5023	1
10-28	ZW414336	Screw, truss head 3x6, w/washer (black)		2
10-29	SK475097	Knob A	LE-6012	2
10-30	SK475121	Knob B	LE-6015	2
10-31x	SC481026	Head Cover Comp.	LE-6025	1
10-32	SC481037	Head Cover	LE-6004	1
10-33	SM481048	Name Plate 4000DS	LE-6005	1
10-34x	ZW312221	Screw, truss head 3x15(black)		2
10-35	SK485651	Head Change Knob C	LE-6027	1
10-36x	ZW434160	Set Screw, hexagon socket 3x3(cup)		1
10-37	SK425158	Pinch Roller Cap	MS-6020	1
10-38x	ZW481072	Washer (SUP)D4x10x0.25t		1
10-39	SK476684	Mech. Knob	LE-6018	2
10-40x	ZW253405	Mech. Knob Screw	7-1-46	2
10-41x	ZW260166	Washer (Nylon) D6.2x13x0.125t		2
10-42	SK314100	Pause Knob B	MR-612	1
10-43x	ZW433001	Set Screw, hexagon socket 3x5(cup)		1
10-44x	EF460146	Fuse ST-4 0.4A	39-1-28	1
10-45	MP204794	Pinch Roller #3	3A-348	1
10-46x	EF277424	Fuse ST-4 0.8A	39-1-28	1
10-47x	EF460146	Fuse ST-4 0.4A (CEE)	39-1-28	1

INDEX

INDEX

SECTION 3

SCHEMATIC DIAGRAM

4000DS SCHEMATIC DIAGRAM

4000DS



4000DS
SCHEMATIC DIAGRAM
1441624A

SERVICE MANUAL

PARTS LIST

AKAI STEREO TAPE DECK

MODEL 4000DS Mk-II

THIS MANUAL MUST BE USED AS A SET TOGETHER WITH SEPARATELY PUBLISHED 4000DS SERVICE MANUAL AND PARTS LIST.

SECTION 1 Except for the parts which have been changed as per List 1 below, the composite parts of Model 4000DS Mk-II are identical to those of Model 4000DS. Therefore, for general repairs and adjustments, etc., please refer to 4000DS Service Manual, and GENERAL OPERATING PRINCIPLES AND ADJUSTMENTS.

1. SPECIFICATIONS

An asterisk next to a figure indicates the minimum guaranteed performance.

TAPE SPEED		7-1/2 and 3-3/4 ips ±2% *7-1/2 and 3-3/4 ips (19 and 9.5 cm/sec) ±3% (7-1/2 ips 1,000 Hz speed standard tape playback)
WOW AND FLUTTER		Less than 0.12% WRMS at 7-1/2 ips *Less than 0.22% RMS at 7-1/2 ips Less than 0.15% WRMS at 3-3/4 ips *Less than 0.30% RMS at 3-3/4 ips (3,000 Hz wow standard tape playback)
TOTAL WOW AND FLUTTER		Less than 0.28% at 7-1/2 and 3-3/4 ips
FREQUENCY RESPONSE	LOW NOISE TAPE	30 to 23,000 Hz ±3 dB at 7-1/2 ips *40 to 20,000 Hz ±3 dB at 7-1/2 ips 30 to 16,000 Hz ±3 dB at 3-3/4 ips *40 to 15,000 Hz ±3 dB at 3-3/4 ips
	WIDE RANGE TAPE	40 to 21,000 Hz ±3 dB at 7-1/2 ips 40 to 16,000 Hz ±3 dB at 3-3/4 ips (Adjust 2 kHz and 20 kHz to same responce. -20 VU recording, using a Scotch #211 tape.)
TOTAL DISTORTION FACTOR		Less than 1.0% at 7-1/2 and 3-3/4 ips *Less than 2.0% at 7-1/2 and 3-3/4 ips (Scotch #211 tape, 1,000 Hz 0 VU recording and playback)
LINE OUTPUT		0.775V (0 dBm ±1 dB) (7-1/2 ips 250 Hz 0 VU standard tape playback)
RECORDING/PLAYBACK LEVEL		0.775V (0 dBm ±1.5 dB) (Scotch #211 tape 1,000 Hz 0 VU recording/playback)
SIGNAL TO NOISE RATIO		Better than 50 dB at 7-1/2 ips Better than 48 dB at 3-3/4 ips
TOTAL SIGNAL TO NOISE RATIO		Better than 44 dB
CROSS TALK	STEREO	Better than 45 dB
	MONAURAL	Better than 60 dB
ERASE RATIO		Better than 70 dB
BIAS FREQUENCY		105 kHz ±5%
INPUT SENSITIVITY/IMPEDANCE	MIC	More than 0.8 mV/30 k ohm
	LINE	More than 70 mV/200 k ohm
	DIN	More than 7 mV/15 k ohm
BIAS LEAK		Less than -30 VU
HIGH FREQUENCY DEVIATION		Within 2 dB (Playback of 3-3/4 ips 8,000 Hz Angle adjustment tape at 7-1/2 ips)
RECORDING CAPACITY		90 minutes stereo recording using an 1,800 ft tape at 7-1/2 ips)
F.FWD AND RWD TIME		4 min and 40 sec at 50 Hz (using 1,800 ft tape)
MOTOR		4-pole induction motor Type: SSM-1 Revolutions: 1,500/1,800 rpm 50/60 Hz
HEAD	ERASE HEAD	Type: E4-200 Gap: 0.6 mm Impedance: 200 ohm ±5% at 100 kHz DC Resistance: 2 ohm
	RECORDING HEAD	Type: R4-150 Gap: 8 micron Impedance: 95 ohm ±15% at 1 kHz DC Resistance: 14.7 ohm
	PLAYBACK HEAD	Type: P4-150 Gap: 1 micron Impedance: 1,050 ohm ±20% at 1 kHz DC Resistance: 94.5 ohm
TRANSISTOR		2SC458LG(C) . . . 4 2SC458LG(D) . . . 2 2SC1096(K)(L) . . . 1 2SC1247A(B)(V) . . . 2 2SC1312R(F)(G) . . . 2 2SC1647(R)(S)(E) . . . 4 2SC1648(R)(S)(E) . . . 4
DIODE		1N34A . . . 2 10D05 . . . 2
ZENER DIODE		WZ240 . . . 1

POWER REQUIREMENTS	JPN	100V AC 50/60 Hz
	CSA	120V AC 60 Hz
	CEE, VDE	220V AC 50 Hz
	BSI	240V AC 50 Hz
	UNIVERSAL	110 to 240V AC 50/60 Hz
POWER CONSUMPTION		40W
DIMENSIONS		407(W) x 314(H) x 196(D) mm (16.2" x 12.6" x 7.8")
WEIGHT		11.1 kg (24.4 lbs.)

NOTE: Specifications subject to change without notice.

1. PRE AMP. P.C. BOARD LE-5623



2. EQUALIZER P.C. BOARD LE-5617



3. SWITCH P.C. BOARD LE-5616



4. POWER SUPPLY & OSC P.C. BOARD LE-5618



5. JACK PLATE P.C. BOARD LE-5626



SECTION 2 The composite parts of Model 4000DS-Mk-II, except for those which have been changes as per the list below, are identical to those of Model 4000DS. Therefore, when ordering parts for this tape deck, please utilize Model 4000DS Parts List.

Ref. No.	Parts No.	Description	Schematic No.	Q'ty
1-1x	BH624385	Head Block Comp.	LE-6	1
1-46x	HZ393974	I-MK Head Terminal Plate	RC-89	1
2-1x	BR589206	Supply Reel Table Block Comp.	LE-3,4,6	1
2-2x	BR657180	Take-up Reel Table Block Comp.	LE-3,4,6	1
2-7	ZG227553	Spring G-2 (L)	900-230	1
2-21	MT292386	Reel Metal Mt. Parts, XR, w/metal	XR-191	1
2-27	ZS434171	Set Screw, hexagon Socket 4x7 (cup/p.)		1
2-36	ZG434092	Spring F4-B	LF-2004	1
2-38	MT228598	Set Sleeve B	CD-66	1
2-39	ZS434160	Set Screw, hexagon Socket 3x3 (cup/p.)		1
2-41	MT368684	Reel Table Disk A	XR-101	1
2-43x	MT255420	Reel Retainer	3R-102	1
2-44x	ZG255633	Reel Spring	3R-109	1
2-45x	MT255565	Reel Shaft Ring	XR-177	1
2-46x	ZW270088	'E' Ring 1.9M	6-1-9	1
3-1x	BM624407	Motor Block Comp.	LE-6	1
6-1x	BZ636996	Tape Guide Block Comp.	LE-6, 1722W/1.	1
6-5	MV447491	Bearing SSR-1950ZZD52		1
6-108	SB258478	REC. Button (Red)	900-167	1
6-110	MC479968	Counter MP-491-28	9-1-23	1
6-116	MI628244	Idler Wheel C	LE-2604	1
6-126	SB485741	Start Button C	MS-1002	1
7-1x	BA624418	Pre-Amp. P.C. Board Comp. (LE-5623A)	LE-6	1
7-TR2	ET623722	Transistor 2SC1648(R)(S)(E)	45-1-178	2
7-TR3	ET623733	Transistor 2SC1647(R)(S)(E)	45-1-179	2
7-TR4	ET539987	Transistor 2SC1312(F)(G)	45-1-133	2
7-TR7	ET623722	Transistor 2SC1648(R)(S)(E)	45-1-178	2
7-TR8	ET623733	Transistor 2SC1647(R)(S)(E)	45-1-179	2
7-L1	EO380564	Ferri Inductor FL7H 1.8 MH(J)	23-1-3	2
7-VR1	EV561442	Semi-fixed/Vol. V10K8-4-2 (4US) 2 kB	36-10-254	2
8-1x	BA624341	OSC, Power Supply P.C. Board Comp.	LE-5618	1
8-TR1	ET453611	Transistor 2SC1096(L)(K)(Z Type)	45-1-109	1
8-TR2,3	ET511920	Transistor 2SC1247A (B)(V)	45-1-131	2
8-D1,2	ED494583	Silicon Diode 10D05	45-2-42	2
8-D3	ED511918	Zener Diode WZ-240	45-6-38	1
8-7x	EZ628413	Heat-sink Plate	LE-5619	1
8-8x	ES494302	Slide SW. CL104B	25-3-79	1
8-9x	EZ624071	Pin For V Connector, w/base RTB-1.5-6	32-1-60	1
8-C6,7	EC558202	Trimmer/C. TM-80A	24-2-26	2
9-116x	BT624058	Power Trans. LET-18	38-4-318	1
9-117x	BT624115	Power Trans. LET-17(CEE)	38-4-321	1
9-118x	BT624126	Power Trans. LET-19(CSA)	38-4-322	1
9-119x	BT624137	Power Trans. LET-20(JPN)	38-4-323	1
9-120x	EJ233370	Socket (Volt, Selector) S-18010	40-2-3	1
9-121x	ES479485	Slide SW. S-1	25-1-66	1
9-122x	ES641092	Slide SW. JE07 (JPN)	25-3-115	1
9-123x	ES480857	Seesaw SW. TV-3 JA-07, w/loose hole	25-2-29	1
9-124x	ES653534	Seesaw SW. JA-02 (CEE)	25-2-43	1
9-125x	EF575932	Fuse 0.8A 250V	39-1-50	1
9-126x	EF238634	Fuse 400MAT (T Type) (CEE)		3
9-127x	EF563681	Fuse 1A 250V (JPN)	39-1-50	3
9-128x	ZW273881	Earth Lug M4 (CEE)		1
9-129x	EA615655	Fuse P.C. Board LE	LE-5312	1
9-130x	EJ624036	2-through Jack	31-2-57	1
9-131x	EJ376604	Mic. Jack 3PMJ1	31-2-17	1
9-132x	MZ628290	REC. Slider	LE-5603	1
9-133x	ZG456186	Lock Lever Spring	CC-1119	1
9-134x	BA628356	EQ. P.C. Board	LE-5617	1
9-135x	ES603696	Seesaw SW. 2C-2P (w/earth)	25-2-36	1
9-136x	ES603707	Seesaw SW. 2C-2P (w/earth)	25-2-37	1
9-137x	ES603707	Seesaw SW. 2C-2P (w/earth)	25-2-37	2
9-138x	EA628367	SW. P.C. Baord	LE-5616	1
9-139x	EV480565	Double Vol. DJ10A 50KAx2	36-3-41	1
9-140x	EV603134	Double Vol. (w/sw.) V24L5DS A50kx2	36-12-7	1
9-141x	EJ603145	Lamp Terminal Plate B	33-2-37	2
9-142x	EL591186	Lamp 6.3V 150MA	28-2-35	2
9-143x	EM480778	VU Meter B-1914R	46-1-57	2
9-144x	SE486865	Lamp Mask B	LE-5035	2
10-1x	BD588745	Mech. Panel Block Comp.	LE-3,6	1
10-3x	BD624240	Mech. Panel Block Comp. (CEE)	LE-6	1
10-4	SP578204	Mech. Panel A-1	LE-6001	1
10-10	SE330895	Counter Escutcheon, MR	MR-646	1
10-11	BC624238	Case Block Comp.	LE-6	1
10-32	SC605823	Head Cover	LE-6030	1
10-35	SK485651	Head Change Knob C	LE-6027	1
10-48x	SP485730	Mech. Panel C (CEE)	LE-6001	1
10-49x	ZS434160	Set Screw, hexagon socket 3x3(cup/p.)		1

When ordering parts, please describe Parts Number, Serial Number, and Model Number in detail.


LEFT
RIGHT
MIC
LINE INPUT
LINE OUTPUT
STEREO HEAD PHONE
PRE AMP P.C BOARD LE-5623
POWER SUPPLY & OSC P.C BOARD LE-5618
TRACK SELECTOR
TAPE SELECTOR
MONITOR
PULL FOR MONO USE
PB LEVEL ADJ
REC SWITCH
SOS
JPN
CSA
CEE VDE
4000DS Mk-II
SCHEMATIC DIAGRAM
NO. 1501422A